# BIZOL ATF Unidrive

Martin-Buber-Straße 12, D-14163 Berlin Tel.: +49 30 804 869 - 0 Fax: +49 30 804 869 - 22 sales@bizol.de www.bizol.com







**BIZOL ATF Unidrive** является HC-синтетической жидкостью последнего поколения для автоматических коробок передач легковых и коммерческих автомобилей, большинства мировых производителей автомобилей.

**Classifications and Specifications**

- Dextron III H/VI*
- Ford Mercon V
- JASO 1-A
- Allison C4
- SP-II (Mitsubishi, Hyundai, Kia)
- SP-III (Mitsubishi, Hyundai, Kia)
- Nissan Matic- D/J/K
- Mazda AFT M- III und M- V
- Toyota T-II, T-IV
- MAN 339 V1/Z1, V2/Z2
- JWS 3309 (Aisin Warner)
- BMW LT 71141; lA 2634; 7045 E; 8072 B (3 er Serie)
- Voith H55.6336
- Subaru ATF
- ZF TE-ML 02F, 03D, 05L, 09,11A
- ZF TE-ML 11B, 14A, 14B, 16L, 17C
- MB 236.1; 236.2; 236.5; 236.6; 236.7; 236.9; 236.10; 236.11
- Daimler NAG-1
- VW G 055 025-A2 und G 052 162-A1

**TECHNICAL DATA**

| Characteristics | ca. Measurement |
|---|---|
| Температура вспышки | 204 °C |
| Вязкость при 100°C | 7,3 мм2/с |
| Плотность при 15 °C | 850 kg/m3 |
| Вязкость при 40°C | 34,4 мм2/с |
| Индекс вязкости | 185 |
| Температура кипения | -48 °C |
| Вязкость при -40°C | <20000 мПа с |
| Цвет | rot |

**AVAILABLE PACK SIZE, ARTICLE, LANGUAGES**

| | |
|---|---|
| 1 l, 4 l, 5 l | on request* |
| 20 l | 27712 |
| 60 l | 27713 |
| 200 l | 27714 |

**INSTRUCTIONS**

Follow the operation instruction of the vehicle and engine manufacturers.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.