BIZOL Diesel Additive

Martin-Buber-Straße 12, D-14163 Berlin Tel.: +49 30 804 869 - 0 Fax: +49 30 804 869 - 22 sales@bizol.de www.bizol.com





Bizol Diesel-Additiv - присадка с улучшителем смазывания является комбинацией действующих веществ с чистящими, диспергирующими и повышающими цетановое число свойствами, предназначенной для современных двигателей, видов топлива и условий эксплуатации. Относится к группе присадки к топливу.

TECHNICAL DATA

Characteristics	ca. Measurement
Температура вспышки	63 °C
Вязкость при 40°C	<7 мм2/с
Цвет	braun
Агрегатное состояние	flüssig
Запах	charakterristisch
Температура кипения	145 ° C
Растворимость в воде	unlöslich
Относительная плотность при 15°C	0,841 г/мл

AVAILABLE PACK SIZE, ARTICLE, LANGUAGES

250 ml 3998

INSTRUCTIONS

Follow the operation instruction of the vehicle and engine manufacturers.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.