BIZOL Penetrating Oil

Martin-Buber-Straße 12, D-14163 Berlin Tel.: +49 30 804 869 - 0 Fax: +49 30 804 869 - 22 sales@bizol.de www.bizol.com

Растворитель ржавчины – эффективное средство для разъединения приржавевших деталей. Высокая приникающая способность. Влагостойкое. Защищает от коррозии. Применяется под любым углом нанесения. Сильная и целенаправленная схема распыления.

TECHNICAL DATA

Characteristics	ca. Measurement
Цвет	Graphit-Schwarz
Запах	Charakteristisch
Щелочность	Mineralöl, Graphit und MoS2
Содержание летучих углеводородов	ca. 70% вес/вес
Относительная плотность при 20°C	0,86 г/мл
Выход	2,33 г/с
Давление паров при 20°C	3 - 4 bar

AVAILABLE PACK SIZE, ARTICLE, LANGUAGES

400 ml 40010

INSTRUCTIONS

Follow the operation instruction of the vehicle and engine manufacturers.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.