BIZOL Hypoid-Getriebeöl GL5 SAE 80W

Martin-Buber-Straße 12, D-14163 Berlin Tel.: +49 30 804 869 - 0 Fax: +49 30 804 869 - 22 sales@bizol.de www.bizol.com





Bizol GL5 SAE 80W является высококачественным автомобильным гипоидным трансмиссионным маслом, соответствующим строжайшим требованиям. Настоятельно предписано для осевых приводов с гипоидной передачей.

Classifications and Specifications

- API GL5
- MAN 342 M-1
- MIL-L 2105 B
- ZF TE-ML 17B

TECHNICAL DATA

Characteristics	ca. Measurement
Температура вспышки	204 °C
Вязкость при 100°C	11,3 мм2/с
Плотность при 15 °C	910 kg/m3
Класс вязкости SAE	80W
Номер цвета ASTM	L3,5
Вязкость при 40°C	98 мм2/с
Зольность сульфатная	0,06 г/100г
Индекс вязкости	101
Температура кипения	-27 °C
Свойства пенообразования	S1B-0/0; S2B-0/0; S3B-0/0
Вязкость при -26°C	<150.000 мПа с
Поташ, оксиды	0,05 г/100г

AVAILABLE PACK SIZE, ARTICLE, LANGUAGES

20 l	4712
60 l	4713
200 l	4714

INSTRUCTIONS

Follow the operation instruction of the vehicle and engine manufacturers.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.