
BIZOL Oil Viscosity Stabilizer

Martin-Buber-Straße 12, D-14163 Berlin Tel.: +49 30 804 869 - 0 Fax: +49 30 804 869 - 22 sales@bizol.de www.bizol.com





Bizol Ölviskositäts-Stabilisator является современной присадкой для бензиновых и дизельных двигателей легковых и грузовых автомобилей. Представляет собой отличную защиту от механического износа, который вызывается разжижением масла при частых холодных запусках двигателя. Благодаря этому значительно повышается надежность работы автомобиля.

TECHNICAL DATA

Characteristics	ca. Measurement
Температура вспышки	101 °C
Цвет	gelb-braun
Агрегатное состояние	pastös
Запах	charakteristisch
Растворимость в воде	unlöslich
Относительная плотность при 20°C	0,87 г/мл
Вязкость при 40°C	4300 мПа с

AVAILABLE PACK SIZE, ARTICLE, LANGUAGES

250 ml 3985

INSTRUCTIONS

Follow the operation instruction of the vehicle and engine manufacturers.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.