

BIZOL New Generation SAE 5W-30



Martin-Buber-Straße 12, D-14163 Berlin Tel.: +49 30 804 869 - 0 Fax: +49 30 804 869 - 22 sales@bizol.de www.bizol.com



BIZOL New Generation SAE 5W-30 is a top class, improved lubricity oil. The excellent combination of HC synthetic base oils with a high-grade additive package (low SAPS etc.) reduces wear losses of the engine and leads to fuel savings. This premium oil is recommended for modern petrol and diesel engines including exhaust aftertreatment with TWC (three-way catalyst) or DPF (diesel particulate filter).

Classifications and Specifications

- ACEA A3/B4-04, C3-04
- API SN / CF
- BMW LL-04
- MB 229.51
- VW 502 00 / 505 00 / 505 01
- Ford WSS M2C917-A

TECHNICAL DATA

Characteristics	ca. Measurement	Method
Температура вспышки	217 °C	
Вязкость при 100°C	11,4 мм2/с	
Вязкость при -30°C	<6600 мПа	
Плотность при 15 °C	855 kg/m3	
Класс вязкости SAE	5W-30	
Номер цвета ASTM	L2,5	
TBN (Общее щелочное число)	7,3 мг KOH/г	
Потери на испарение	9,8 Вес -/%	
Вязкость при 40°C	67,6 мм2/с	
Зольность сульфатная	0,8 г/100г	
Индекс вязкости	165	
Температура кипения	-37 °C	
Вязкость при высоких скоростях сдвига / высокой температуре	3,5 мПа с	
16 мм ширина в свету - 20 °C	67,6 бар/м	

AVAILABLE PACK SIZE, ARTICLE, LANGUAGES

1 l	5110
1 l	95110
4 l	5116
4 l	95116
5 l	95111
20 l	5112
60 l	5113
200 l	5114

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

BIZOL New Generation SAE 5W-30



Martin-Buber-Straße 12, D-14163 Berlin Tel.: +49 30 804 869 - 0 Fax: +49 30 804 869 - 22 sales@bizol.de www.bizol.com

INSTRUCTIONS

Follow the operation instruction of the vehicle and engine manufacturers.